



AVAILABLE AS

B0006CGZ without battery and charger

PRODUCT HIGHLIGHTS



Effortless connectivity
The tool's battery adapter connects seamlessly by inserting the connector into the tool, facilitated by a large lever for easy one-hand attachment and detachment



Speed control dial
Enables the selection of rotation speed to suit various workpieces

1. 6.000 min⁻¹
2. 6.500 min⁻¹
3. 8.000 min⁻¹
4. 9.500 min⁻¹
5. 10.000 min⁻¹



Dust Collection Options
This tool offers flexible dust collection options, allowing users to choose between self dust collection with an attached dust bag or enhanced dust control by connecting to a vacuum cleaner, depending on the application needs



Optimal Control and Maneuverability
Designed for precision, the tool's handle is positioned close to the sanding surface and has an optimally balanced center of gravity, ensuring excellent maneuverability for fine operations.

NOISE AND VIBRATION

Sound pressure level: **76 dB(A)**
Vibration level: **2,6 m/s²**


COMPATIBILITY

Recommended: **BL4020, BL4025, BL4040, BL4040F, PDC01, PDC1200, PDC1500**
Compatible: **BL4050F and BL4080F**

RELATED PRODUCTS



XGT 40 V max
B0002CG
Battery powered
random orbit sander



XGT 40 V max
B0004CG
Battery powered
random orbit sander



LXT 18 V
DB0480
Cordless finishing
sander

USER BENEFITS

- Suitable for carpenter, craftsmen and contractors
- Excellent maneuverability is achieved through a connector-style battery connection that reduces hand load and keeps the overall height low
- Lightweight and low height design makes it similar to pneumatic sanders, ensuring ease of use and portability.
- Optimal handle design places the handle close to the sanding surface with a balanced center of gravity for precise control during fine operations.
- Versatile connector structure allows for easy switching between different sanding applications, like large surfaces and corners.
- High efficiency and power are provided by the 40 V max XGT Li-Ion battery with a BL motor, ensuring stable sanding with consistent speed control.
- Low maintenance and longevity are achieved without the need for air compressors, periodic lubrication, or maintenance, reducing downtime and increasing productivity.
- The tool also features soft start, variable speed control, constant speed control, an electric brake, and an anti-restart function.

TECHNICAL SPECIFICATIONS

Accumulator voltage	40 V max - XGT
Orbits per minute	6.000 - 10.000 min ⁻¹
Orbit diameter	ø 3 mm
Abrasive triangular paper pad	100 x 150 mm
Power supply cord	1,6 m
Dimensions (L×W×H)*	263 x 100 x 99 mm
Weight*	0,93 kg

* without power supply cord and battery adapter


ACCESSORIES

<p>Battery adapter - 1,6 m 1914H3-6</p> 	<p>Battery adapter - 5 m 1914H5-2</p> 	<p>Protection cover 1914H7-8</p> 
<p>Harness 1914H8-6</p> 	<p>Triangle pad 1914J0-6</p> 	<p>Square pad 1914H9-4</p> 
<p>Dust bag 122G32-0</p> 	<p>AWS unit WUT01 198900-7</p> 	<p>Wireless unit adapter WUT02 & WUT01 199790-1</p> 
<p>Arm band 194679-8</p> 		



MAKITA d.o.o.,
Brnčičeva 17, 1231 Ljubljana-Črnuče, Slovenia
T: +386 (0) 59 083 600, E: info@makita.si



AVAILABLE AS
BS001GZ without battery and charger

PRODUCT HIGHLIGHTS


Optimal weight balance
The battery is positioned above the sanding belt on the front side of the tool, ensuring that the sanding pressure is evenly applied to the sanding surface.



Stationary use (installed upside down)
The tool has a flat surface on top of the housing, allowing it to be used as a stationary belt sander when combined with the optional Clamp Complete and Guide Rule Set accessories.



Angle adjustable front handle
Sanding to the edge of the wall is possible by positioning the front handle either vertically at 0 degrees or angled 30 degrees to the rear.



Angle adjustable LED job light
The tool features twin LEDs with an afterglow function, providing enhanced visibility. The LEDs can be adjusted to an angle of 45 degrees, allowing for optimal lighting in various working conditions.

NOISE AND VIBRATION

Sound pressure level: **87 dB(A)**,
Sound power level: **95 dB(A)**, Vibration level: **2,5 m/s²**

COMPATIBILITY

Recommended: **BL4040F, BL4040, BL4025, BL4020, PDC1500, PDC1200**. Compatible: **BL4080F, BL4050F**

USER BENEFITS

- Suitable for professional woodworkers and contractors.
- Automatic belt position adjustment ensures the sanding belt stays in the correct position during operation, reducing the need for manual adjustments.
- Dust bag with anti-drop feature is equipped with a lock mechanism to prevent the dust bag from falling off, even when the tool is used vertically.
- High power offers performance similar to or superior to corded models, ensuring efficient and powerful sanding.
- Lock-on / Lock-off function enhances continuous operation with the lock-on function and prevents unintentional activation with the lock-off lever on the trigger.
- Variable speed control by dial enables precise control over the sanding speed to match different materials and applications.
- Flush sanding capability allows for sanding flush to the front and right side, making it easier to work on edges and corners.

TECHNICAL SPECIFICATIONS

Accumulator voltage	XGT 40 V max
Belt size	76 x 533 mm
Belt speed	120 - 470 m/min
Variable speed control by dial	✓
Dimensions (L×W×H)*1	440 x 148 x 165 mm
Weight*2	4,5 kg

*1 With BL4040 battery | *2 with BL4020 battery

ACCESSORIES

Clamp complete
192694-6



Guide rule
1915E3-1



Sanding shoe
193070-7



Carbon plate
193197-3



Cork rubber plate
193199-9



WUT01 - auto start wireles unit
198900-7



WUT02 - Wireles unit adapter
199742-2



WUT02 + WUT01 - Wireles unit adapter
199790-1


RELATED PRODUCTS


LXT 18 V
DBS180
Cordless belt sander



1.200 W
9403
Belt sander



1.010 W
9404
Belt sander



AVAILABLE AS

CE003GZ02 without battery and charger

USER BENEFITS

- Suitable for dry and wet heavy duty concrete cutting.
- Lightweight and compact, yet capable of high-speed, powerful cutting.
- AFT - Active Feedback sensing Technology shuts down current to the motor, if the rotation speed suddenly slows down (in the case of kick-back, etc.).
- Lock-off button minimizes accidental start up.
- Equipped with an electric brake that quickly stops the wheel for maximum productivity.
- Overload protection alerts the operator with a blinking red LED to reduce unnecessary battery recharging.

TECHNICAL SPECIFICATIONS

Accumulator voltage	40 V max XGT
No load speed	6.600 min ⁻¹
Blade / hole Ø	230 / 22,23 mm
Blade thickness	3,0 mm
Max cutting capacity	88 mm
Dimensions (L×W×H)	603 x 240 x 350 mm
Weight*	6,4 kg

* With BL4040F battery

PRODUCT HIGHLIGHTS



Anti-vibration housing
2 rubber pieces placed around the motor reduce the vibration during cutting.



Rotatable guard
The position of the guard can be adjusted to suit the working posture.



Wet cutting
Water supply kit can be connected to reduce the generation of dust during cutting.



LED job light
Enables work in badly lit conditions and is easily turned on/off with the button located on the top of the tool.

ACCESSORIES

Vacuum brazed segmented diamond wheel for rescue
B-55326



Coupling sleeve
123121-2



Segmented diamond wheel for concrete
E-02967



Thin abrasive cut-off wheel for stainless steel
E-03006



NOISE AND VIBRATION

Sound pressure / power level: **105 / 116 dB(A)**
Vibration level: **3,0 m/s²**

COMPATIBILITY

Recommended: **BL4080F, BL4050F, BL4040F**
Compatible: **BL4040**

RELATED PRODUCTS



XGT 40 + 40 V max
CE001G
Cordless power cutter
- wet/dry 355 mm



XGT 40 + 40 V max
CE002G
Cordless power cutter
- dry 355 mm



LXT 18 + 18 V
DCE090
Cordless power cutter
- wet/dry 230 mm



MAKITA d.o.o.,
Brnčičeva 17, 1231 Ljubljana-Črnuče, Slovenia
T: +386 (0) 59 083 600, E: info@makita.si



USER BENEFITS

- Suitable for outdoor adventures, homeowners and gardeners.
- Compact and ergonomic design for easy handling
- Sufficient cleaning power for light-duty tasks on work sites and for home use
- Three types of water supply methods: water faucet (for high water volume), self-priming (for distant water sources), and plastic bottle (when no other water source is available)
- Two power modes (High/Low) selectable depending on applications
- 5-in-1 nozzle allows for easy mode changes by rotating the nozzle head
- Battery capacity warning function with a lamp indicating low or empty battery

TECHNICAL SPECIFICATIONS


Accumulator voltage	LXT 18 V
Regular pressure (2./1.)	24 / 8 bar (faucet) 20 / 8 bar (self priming)
Regular flow rate (2./1.)	2,5 / 1,5 l/min
Supplied hose length	6 m
Max feed temperature water	40 °C
Attachment shank	D type
Run time (2./1.)*1	18/50 min
Dimensions (L×W×H)*2	888 x 99 x 239 mm
Weight*3	2,7 kg

*1 With BL1830B battery | *2 with extension pipe and end nozzle | *3 with BL1860B battery

AVAILABLE AS

DHW180Z without battery and charger

PRODUCT HIGHLIGHTS



5-in-1 nozzle

5-in-1 nozzle allows for easy mode changes by rotating the nozzle head.

1. For block or concrete walls and outdoors surfaces
2. For cars and bicycles
3. For window glasses and exterior walls
4. For bathrooms and sashes
5. For watering flowers and plants



Three types of water supply methods

1. Water faucet
2. Self-priming
3. Plastic bottle (optional accessory (LX00000004))



Lightweight & compact design

Easy-to-handle handgun style, yet provides sufficient cleaning power for light-duty washing tasks on work sites and for home use.

ACCESSORIES

Foam nozzle
LX00000001



Angle nozzle
LX00000002



Brush
LX00000003



Water bottle adapter
LX00000004



NOISE AND VIBRATION

Sound pressure level: **84 dB(A)**



COMPATIBILITY

Recommended: **BL1815N, BL1820B, BL1830B, BL1840B, BL1850B and BL1860B**

RELATED PRODUCTS



XGT 40 V max
HW001G
Cordless high pressure washer



LXT 18 + 18 V
DHW080
Cordless high pressure washer



MAKITA d.o.o.,
Brnčičeva 17, 1231 Ljubljana-Črnuče, Slovenia
T: +386 (0) 59 083 600, E: info@makita.si



USER BENEFITS

- Suitable mainly for metal drilling operations
- High-power motor for heavy-duty applications.
- Extended service life of carbon brush
- Improved durability against wobbling spindle.
- Large trigger with variable speed control.
- Lock-on button for continuous operation.
- Forward / reverse switch for easy switching between operating modes.
- Suitable for drill stands.

TECHNICAL SPECIFICATIONS

	DP4020	DP4021
Drill chuck type	keyed	keyless
Continuous rating input	630 W	
No load speed	0-3.000 min ⁻¹	
Chuck capacity	1,5-13 mm	
Drilling capacity Ø: steel	13 mm	
Drilling capacity Ø: wood	30 mm	
Dimensions (L×W×H)	269 x 66 x 209 mm	271 x 66 x 209 mm
Weight	1,9 kg	1,8 kg

PRODUCT HIGHLIGHTS



Drilling capacity
 Steel: 13 mm
 Step / cone drill bit: 32 mm
 Hole saw: 76 mm
 Wood: 30 mm
 Ship auger bit: 30 mm
 Self feeding bit: 51 mm



Extended service life
 A brush holder unit was added for improved service life of the carbon brush compared to our current models, and realized the same power in the reversed rotation as in the forward rotation.



Improved durability
 By adopting a metal bearing bracket it improved the durability of the bearing section against a wobbling spindle during drilling.



Lock-on button
 Easy to reach lock-on button for continuous operation.

ACCESSORIES

Side handle
1914C4-9



HSS-TiN metal drill bit set -
2 / 3 / 4 / 5 / 6 / 8 mm
D-77241



NOISE AND VIBRATION

Sound pressure / power level: **84 / 92 dB(A)**
 Vibration level: **3,5 m/s²**

RELATED PRODUCTS



750 W
DP4003
 Drill



720 W
DP4011
 Drill



MAKITA d.o.o.,
 Brnčičeva 17, 1231 Ljubljana-Črnuče, Slovenia
 T: +386 (0) 59 083 600, E: info@makita.si

www.makita.si

LXT**DRT52****CORDLESS TRIMMER****BL MOTOR XPT****AVAILABLE AS**

DRT52Z without battery and charger

USER BENEFITS

- Suitable for smaller applications in carpentry and woodworking.
- Equipped with Lock/unlock button, which minimizes the chance of unexpected start-ups.
- Soft start function minimizes start-up shock by making the tool start smoothly.
- Brushless motor provides output efficiency similar or superior to that of our corded models.
- LED indicator for unlocked/stand-by mode.
- Smooth and precise depth adjustment.

TECHNICAL SPECIFICATIONS

Accumulator voltage	18 V LXT
No load speed	30.000 min ⁻¹
Collet chuck Ø	6 mm
Plunge capacity	0-42 mm
Dimensions (L×W×H)	134 x 90 x 220 mm
Weight*	1,6 kg

* With BL1860B battery

PRODUCT HIGHLIGHTS

Transparent plastic base
For clear view of the trimming edge.



Depth adjustment mechanism
Rack and pinion mechanism ensures smooth and precise depth adjustment.



Rubberized soft grip
Provides a secure grip for better tool handling.



LED indicator
LED lamp lights up solid to indicate that the tool is in standby mode; unlocked and ready to be used.

ACCESSORIES

Trimmer guide
122703-7



Template guide 10
343577-5



Straight guide
122704-5



Chip deflector
418647-0

**NOISE AND VIBRATION**

Sound pressure / power level: **81 / 89 dB(A)**
Vibration level: **2,5 m/s²**

**COMPATIBILITY**

Recommended: **BL1860B, BL1850B, BL1840B**
Compatible: **BL1830B, BL1820B, BL1815N**

RELATED PRODUCTS

LXT 18 V
DRT50
Cordless trimmer



530 W
3711
Trimmer

MAKITA d.o.o.,
Brnčičeva 17, 1231 Ljubljana-Črnuče, Slovenia
T: +386 (0) 59 083 600, E: info@makita.si

www.makita.si



DTC102

DTC103

AVAILABLE AS

DTC102ZK with plastic case, without battery and charger | DTC103ZK with plastic case, without battery and charger

PRODUCT HIGHLIGHTS



Cutting completed

Forward switch OFF

Blade stops at set position

Cutting completed

Automatic reverse function

- Auto-reverse function when a cut has been completed.
- After cutting, the motor stops and the blade automatically returns to the set position when the forward switch is released.



Opening angle setting dial
6 stages (ø10 - 50 mm).
Blade return volume can be adjusted to suit the diameter of the cable to be cut.



LED job light
One LED with afterglow function.

USER BENEFITS

- Suitable for professionals in the electrical construction industry.
- **DTC102:** Designed for cutting aluminum (Al) and copper (Cu) cables.
- **DTC103:** Designed for cutting Aluminum Conductors Steel Reinforced (ACSR).
- Specially developed for cutting, featuring a lightweight design for excellent maneuverability.
- The movable blade automatically returns to the set position after cutting is completed.
- Adjustable blade return volume: The blade opening angle can be adjusted to suit the diameter of the cable being cut.
- Equipped with one LED job light with an afterglow function

TECHNICAL SPECIFICATIONS

	DTC102	DTC103
Accumulator voltage	LXT 18 V	
Max blade opening width	65 mm	54 mm
Max cable cutting capacity	Non-ferrous materials only (Al or Cu) ø 65 mm	ACSR Al: 550 mm ² ST: 70 mm ²
Dimensions (L×W×H)*	116 x 240 x 401 mm	
Weight*	3,5 kg	5,5 kg

* With BL1860B battery

ACCESSORIES

Shoulder belt
127759-5



NOISE AND VIBRATION

Sound pressure level: **69,5 dB(A)**,
Sound power level: **78,1 dB(A)**, Vibration level: **0,3 m/s²**



COMPATIBILITY

Recommended: **BL1815N, BL1820B, BL1830B, BL1840B, BL1850B and BL1860B**

LXT**DTD173****CORDLESS IMPACT DRIVER****BL MOTOR XPT****AVAILABLE AS**

DTD173Z without battery and charger | DTD173RTJ with 2x BL1850B battery, DC18RC charger and Makpac 2 case

USER BENEFITS

- Suitable for construction and carpentry, automotive repair, electrical and plumbing, and DIY enthusiasts.
- 4-speed power selection and 4 assist modes for a variety of applications.
- Variable speed control by trigger.
- Compact design with a slim tool body and an overall length of 111 mm.
- Optimal tool balance achieved by moving the battery 12 mm backward, thus moving the center of gravity closer to the center line of the grip.
- Two ball bearings are used to securely hold the anvil, reducing bit wobbling.

TECHNICAL SPECIFICATIONS

Accumulator voltage	LXT 18 V
No load speed	0-1.100 / 2.100 / 3.200 / 3.600 min ⁻¹
Impacts per min	0-1.100 / 2.600 / 3.600 / 3.800 min ⁻¹
Hex shank	1/4"
Standard bolt / machine screw	M5-M16 / M4-M8
High strength bolt / coarse thread screw	M5-M14 / 22-125 mm
Max. fastening torque	180 Nm
Dimensions (L×W×H)	111 x 81 x 234 mm
Weight* ¹	1,5 kg

* With BL1860B battery

PRODUCT HIGHLIGHTS**Ring LED**

Evenly distributed illumination thanks to a ring shaped LED work light with 3 brightness settings.

**Accessible control panel**

Located at the rear side of the tool allowing the user to check and change the mode during operation.

**Quick mode button**

Located at the top of the trigger switch to quickly toggle between 4 levels of impact force or between application modes.

**4 assist modes**

wood: tightening long screws
bolt: loosening bolts
T1: teks screw into thin metal
T2: teks screw into thick metal

ACCESSORIES

Battery protector
for 3,0 / 4,0 / 5,0 / 6,0
Ah LXT batteries
194649-7



Hook - long
for 3,0 / 4,0 / 5,0 / 6,0
Ah LXT batteries
346317-0



Hook - short
for 1,5 / 2,0 Ah
LXT batteries
346449-3



Inner tray for Makpac case
wood: 837670-0



Makpac case type 2
821550-0

**NOISE AND VIBRATION**

Sound pressure level: **100 dB(A)**, Sound power level: **108 dB(A)**, Vibration level: **12,9 m/s²**

**COMPATIBILITY**

Recommended: **BL1815N, BL1820B, BL1830B, BL1840B, BL1850B and BL1860B**

RELATED PRODUCTS

LXT 18 V
DTD172
Cordless impact driver



XGT 40 V max
TD001G
Cordless impact driver



XGT 40 V max
TD002G
Cordless impact driver

MAKITA d.o.o.,
Brnčičeva 17, 1231 Ljubljana-Črnuče, Slovenia
T: +386 (0) 59 083 600, E: info@makita.si

www.makita.si

LXT**DTW1004XV****CORDLESS IMPACT WRENCH****BL MOTOR XPT****AVAILABLE AS**

DTW1004XVZ without battery and charger

USER BENEFITS

- Suitable for use near high-voltage electrical power lines.
- DTW1004 has been developed by replacing the socket retention mechanism of DTW1002 with a pin detent mechanism for more secure retention.
- Overall length is extremely shortened.
- Electronic 3 stage impact power selection reduces fault tightening.
- Hammer case securely fastened with four bolts.
- Twin LED job light with preglow and afterglow functions.
- Efficient impact system with less vibration.
- Easy-to-operate, push button type F/R change switch
- Electric brake stops the rotation gently but fast, allowing user to quickly resume operation.
- Variable speed control by trigger
- Hook for operator convenience

TECHNICAL SPECIFICATIONS

Accumulator voltage	LXT 18 V
Output power*	620 W
No load speed	0 - 900/1.000/2.000 min ⁻¹
Impacts per min	0 - 1.800 /2.000 /2.400 min ⁻¹
Nut-busting torque	1.300 Nm
Max fastening torque	1.050 Nm
Square drive	1/2"
Dimensions (L×W×H)	223 x 91 x 289 mm
Weight*	3,4 kg

* With BL1860B battery

PRODUCT HIGHLIGHTS

Twin LED job light
With preglow and afterglow functions.



Electronic 3 stage impact power selection



Hook for operator convenience



Pin detent mechanism
The socket retention mechanism has been replaced with a pin detent mechanism for more secure retention.

ACCESSORIES

Impact deep socket assortment
E-16586



Extension
75 / 100 / 150 / 250 mm
134874-8



Extension handle
191667-2



Joint
134877-2

**NOISE AND VIBRATION**

Sound pressure level: **98 dB(A)**, Sound power level: **106 dB(A)**
Vibration level: **18.4 m/s²**

**COMPATIBILITY**

Recommended: **BL1860B, BL1850B, BL1840B, BL1830B, BL1820B, BL1815N**

RELATED PRODUCTS

40 V max XGT
TW001G
Cordless Impact Wrench



18 V LXT
DTW1002
Cordless Impact Wrench

MAKITA d.o.o.,
Brnčičeva 17, 1231 Ljubljana-Črnuče, Slovenia
T: +386 (0) 59 083 600, E: info@makita.si

www.makita.si



AVAILABLE AS

DUA200Z without battery and charger

USER BENEFITS


- Suitable for gardeners and arborists.
- Powerful performance for easy pruning of high branches.
- Excellent tool balance and high work efficiency due to the brushless motor and lightweight tool head.
- Head angle adjustment in 9 stages between 60° upwards and 60° downwards with a one-touch lock/unlock mechanism.
- Slim tool head design for easy insertion between branches.
- Segmented pole allowing total length adjustment to either 1,6 m or 2,5 m, fixed without tools.
- Tool-less chain adjustment with automatic tension adjustment by loosening and retightening the lever.
- Branch hook for pulling and dropping cut branches.

TECHNICAL SPECIFICATIONS

Accumulator voltage	LXT 18 V
Guide bar length	200 mm
Output power	0,26 kW
Chain pitch	0,325"
Chain gauge	1,1 mm
Chain speed	6,7 m/s
Oil tank capacity	55 ml
Blade angle adjustment	60° up / 60° down (9 stages)
Dimensions (L×W×H)*1	1.620 / 2,520 x 85 x 134 mm
Weight**2	3,5 kg

*1 without guide bar | **2 with BL1860B battery

PRODUCT HIGHLIGHTS



Head angle adjustment
The tool head angle can be adjusted in 9 stages, ranging from 60° upwards to 60° downwards. The angle adjustment can be locked or unlocked with a single touch



Pole of segmented pipes
The pole consists of segmented pipes, allowing the total length of the tool to be adjusted to either 1,6 m or 2,5 m



Slim tool head
The slim shape of the tool head, 74 mm in width, allows for easy insertion between branches.



Branch hook
A hook designed for pulling and dropping branches that have been caught.

ACCESSORIES

<p>Guide bar - 200 mm 1914S3-3</p>	<p>Saw chain (38 / 1,1 mm / ,325" LP / MC) 1914S1-7</p>	<p>Strap 122D94-0</p>
<p>Sharpening set (ø 4 mm) D-72154</p>	<p>Biotope chain oil - 1 l 1910U0-9</p>	<p>Mineral chain oil - 1 l 195093-1</p>

NOISE AND VIBRATION

Sound pressure level: **79 dB(A)**, Sound power level **87 dB(A)**
Vibration level: **2,5 m/s²**

COMPATIBILITY

Recommended: **BL1815N, BL1820B, BL1830B, BL1840B, BL1850B, BL1860B and PDC01**

RELATED PRODUCTS

XGT 40 V max UA0036
Cordless pole chain saw

XGT 40 V max UA0046
Cordless telescopic chain saw

LXT 18 + 18 V DUA301
Cordless telescopic chain saw

EY403MP
Chain saw attachment for multi-function power head



MAKITA d.o.o.,
Brnčičeva 17, 1231 Ljubljana-Črnuče, Slovenia
T: +386 (0) 59 083 600, E: info@makita.si



USER BENEFITS

- Suitable for metal grinding operations.
- The side grip can be attached closer to the center of the wheel rotation for improved maneuverability in grinding operation.
- More light weight and compact compared to it's predecessor.
- Reduced core abrasion: stator core abrasion is reduced by adding a water absorption process to the nylon motor housing after molding to reduce dimensional changes of the housing in humid conditions.

TECHNICAL SPECIFICATIONS

Continuous rating input	2.200 W
No load speed	6.600 min ⁻¹
Wheel Ø	230 mm
Hole Ø	22,23 mm
Wheel cover mount	3 grooves
Wheel cover attachment type	clamp
Dimensions (L×W×H)	438 x 250 x 144 mm
Weight	7,4 kg

PRODUCT HIGHLIGHTS



Three handle positions
Multiple attachment points for the handle for different handle positions or the optional use of a loop handle.



Large trigger type switch
Easy to operate even with gloves.

ACCESSORIES

Wheel cover for abrasive cut-off wheel
122913-6



Loop handle
199176-9



Abrasive cut-off wheel for metal
A-85335



Wheel cover for grinding wheel
122891-0



Anti-vibration handle
162264-5



NOISE AND VIBRATION

Sound pressure / power level: **93 / 101 dB(A)**
Vibration level: **7,0 m/s²**

RELATED PRODUCTS



2.200 W
GA9020
Angle grinder



2.200 W
GA9020RF
Angle grinder



MAKITA d.o.o.,
Brnčičeva 17, 1231 Ljubljana-Črnuče, Slovenia
T: +386 (0) 59 083 600, E: info@makita.si

www.makita.si

XPT



AVAILABLE AS

ML012G without battery and charger | **DML818** without battery and charger

USER BENEFITS

- Suitable for electricians, technicians, automotive mechanics, construction workers, DIY enthusiasts, and field workers who need portable, reliable lighting for inspections, repairs, and various tasks in low-light conditions
- Adjustable brightness with three levels: strong, medium, weak
- Compact and portable for easy transport and storage
- Multiple hanging options with strap holes and metal hook
- Wide-area illumination with 630 mm length and light diffusion lens, up to 1.700 lumens
- Adjustable angles with 7-step, 45-degree increments
- Dual-sided lighting capability when folded
- Water and dust resistant
- Battery features include depletion alert and memory function

TECHNICAL SPECIFICATIONS

	ML012G	DML818
Accumulator voltage	XGT 40 V max	LXT 18 V
Luminous flux	1.700/800/400 lm	
Luminance	2.000/1.000/450 lx	
Color temperature	Daylight white - 5.000 K	
Runtime (max brightness setting)	7 h*1	5 h*2
Dimensions (L×W×H)	1.130 - 1.900 x 85 x 100 mm	1.130 - 1.900 x 80 x 101 mm
Weight	2 kg*1	1,7 kg*2

*1 with BL4040 battery / *2 with BL1860B battery


PRODUCT HIGHLIGHTS




Foldable
The LED light bar section can be folded in half, allowing for double-sided illumination when folded. Compact for transportation or storage



Illuminating angle adjustment by rotating the LED light bar
By rotating the LED light bar clockwise up to 90 degrees or counterclockwise up to 180 degrees, the user can adjust the illuminating angle to 7 different positions




Telescopic hook
Clips on each end of the telescopic hook hold the LED light bar section securely attaches to the hood, back door, and more, making it ideal for automotive workshops.



Illumination mode selection switch

- 1. All 42 LEDs on
- 2. Lower 24 LEDs on
- 3. Upper 18 LEDs on

ACCESSORIES



XGT COMPATIBILITY

Recommended: **BL4020, BL4025, BL4040, BL4040F, BL4050F and BL4080F**

LXT COMPATIBILITY

Recommended: **BL1815N, BL1820B, BL1830B, BL1840B, BL1850B and BL1860B**

RELATED PRODUCTS



XGT 40 V max
ML002G
Cordless worklight



XGT 40 V max
ML007G
Cordless flashlight



XGT 40 V max / LXT 18 V
ML010G
Cordless area worklight



LXT 18 V
DML816X
Cordless worklight



LXT 18 V
DML814
Cordless area worklight



MAKITA d.o.o.,
Brnčičeva 17, 1231 Ljubljana-Črnuče, Slovenia
T: +386 (0) 59 083 600, E: info@makita.si

-  Bluetooth®
-  AUX IN jack
-  Qualcomm® aptX™ HD
-  Qualcomm® aptX™



USER BENEFITS

- Suitable for job sites and outdoor activities.
- High-quality sound with powerful deep bass.
- Featuring Qualcomm® aptX™ and Qualcomm® aptX™ HD that support high resolution Bluetooth wireless audio.
- Equipped with a dedicated microphone jack for use as a microphone amplifier speaker.
- Class 1 Bluetooth transmission power with 30 m guaranteed and 100 m communicable transmission distance.
- USB output port for charging of mobile phones and other smart devices.
- Equalizer (FLAT, JAZZ, ROCK, CLASSIC, POP, NEWS, My equalizer).
- Color LCD screen.

TECHNICAL SPECIFICATIONS

Power supply	XGT 40 V max / LXT 18 V / AC
Continuous run time*1	47 h with BL4040F/ 43 h with BL1860B
Bluetooth	✓
AUX-in	✓
Microphone input port	✓
USB output port	✓
Dimensions (L×W×H)	243 x 236 x 205 mm
Weight*2	4,8 kg

*1 With bluetooth and the front LED turned off | *2 with BL4040 battery

AVAILABLE AS

MR014G with AC adapter

PRODUCT HIGHLIGHTS



Connect multiple speakers
Enables you to connect up to 10 speakers.
2 connected speakers: stereo sound.
3 or more speakers: mono sound.



Smartphone stand
You can place your smartphone on the top of the speaker by fixing the handle at the angle to support the back of the phone.



Decorative LED light
You can choose the light to be on/off or blink to the music.



IP65 rated protection
Battery storage cover and rubber terminal covers protect the speaker from dust and water.

XGT COMPATIBILITY

Recommended: **BL4020, BL4025, BL4040, BL4040F**

LXT COMPATIBILITY

Recommended: **BL1815N, BL1820B, BL1830B, BL1840B, BL1850B and BL1860B**

RELATED PRODUCTS



LXT / CXT / AC
DMR203
Cordless Bluetooth speaker



XGT / LXT / CXT / AC
MR002G
Cordless Bluetooth radio



XGT / LXT / CXT / AC
MR004G
Cordless Bluetooth radio



XGT / LXT / CXT / AC
MR007G
Cordless Bluetooth radio



MAKITA d.o.o.,
Brnčičeva 17, 1231 Ljubljana-Črnuče, Slovenia
T: +386 (0) 59 083 600, E: info@makita.si


AVAILABLE AS

PP001GZK without battery and charger and with plastic case

USER BENEFITS

- Suitable for fast punching of round and oval holes without sparks or chips.
- Able to punch into a wide range of materials (mild steel, stainless steel, aluminium and copper) and structures (flat, angle, and H bar or channel).
- Adjustable depth guide enables the punch location to be adjusted up to 40 mm from the edge.
- 19 mm shorter compared to the 18V LXT model.
- 40V max XGT battery and a high-power BL motor deliver operating speed 85% faster compared to the 18V LXT model.

TECHNICAL SPECIFICATIONS

Accumulator voltage	XGT 40 V max
Max. capacity	20 mm / 14x21 mm
Hole shape	round / oval
Max. thickness - steel	9 mm
Max. thickness - stainless steel	6 mm
Max. throat depth	40 mm
Dimensions (L×W×H)*1	296 x 40 x 99 mm
Weight*1	11,6 kg

*1 With BL4025 battery

PRODUCT HIGHLIGHTS


Productivity
The punch automatically retracts once the hole is complete for efficient continuous punching.



Return lever
Return lever allows for the punch to be retracted during mid operation.



Convenience
360° rotatable grip handle for optimal positioning in a variety of spaces.



Maximal thickness for round holes
Is able to punch 19 mm round holes in general steel the thickness of 10 mm.

ACCESSORIES

Hydraulic oil
SC00000106



Work stand
SC03801080



Slide stopper
SC03300790



Punch / die
round holes



Punch / die
oval holes



Round Hole Size	Part No.	Part No.	Oval Hole Size	Part No.	Part No.
6 mm	SC05340040	SC05340040	6,5×10 mm	SC05340200	SC00000244
6,5 mm	SC05340050	SC05340050	6,5×13 mm	SC05340210	SC00000246
8 mm	SC05340060	SC05340060	8,5×13 mm	SC05340220	SC00000248
8,5 mm	SC05340070	SC05340070	8,5×17 mm	SC05340230	SC00000250
10 mm	SC05340080	SC05340080	9×13,5 mm	SC05340240	SC00000252
11 mm	SC05340090	SC05340090	9×18 mm	SC05340250	SC00000254
12 mm	SC05340100	SC05340100	10×15 mm	SC05340260	SC00000256
13 mm	SC05340110	SC05340110	10×20 mm	SC05340270	SC00000258
14 mm	SC05340120	SC05340120	11×16,5 mm	SC05340280	SC00000260
15 mm	SC05340130	SC05340130	12×18 mm	SC05340290	SC00000262
16 mm	SC05340140	SC05340140	13×19,5 mm	SC05340300	SC00000264
18 mm	SC05340150	SC05340150	14×21 mm	SC05340310	SC00000266
19 mm	SC05340170	SC05340170			
20 mm	SC05340160	SC05340160			


NOISE AND VIBRATION

Sound pressure level: **77 dB(A)**,
Vibration level: **2,5 m/s²**


COMPATIBILITY

Recommended: **BL4020, BL4025, BL4040, BL4040F, BL4050F, BL4080F**

RELATED PRODUCTS


LXT 18 V
DPP200
Cordless hole
puncher



AVAILABLE AS

RP001GZ without battery and charger

PRODUCT HIGHLIGHTS



Simple switch operation

1. Lock-off button
2. Lock-on button
3. Trigger switch



3-stage cut depth adjustment

Select the stopper screw by rotating the stopper base.



Speed control dial

Enables the selection of rotation speed to suit various workpieces

1. 8.000 min⁻¹
2. 12.500 min⁻¹
3. 17.000 min⁻¹
4. 21.000 min⁻¹
5. 25.000 min⁻¹



LED job light

Pressing the lock-off button turns the tool on in standby mode, with the LED job light providing better visibility of the cutting position.



NOISE

Sound pressure level: **92 dB(A)**, Sound power level: **100 dB(A)**,
Vibration level: **6,3 m/s²**



COMPATIBILITY

Recommended: **BL4050F, BL4040F, BL4040, BL4025** and **BL4020** | Compatible: **BL4080F**

RELATED PRODUCTS



XGT 40 V max
RT001G
Cordless trimmer



XGT 40 V max
VC004G
Cordless vacuum cleaner - AWS



XGT 40 V max
VC009G
Cordless backpack vacuum cleaner - AWS

USER BENEFITS

- Suitable for carpenters, cabinet makers, craftsmen, and contractors.
- Maneuverable and efficient with a lightweight, low-height design that maintains corded model efficiency.
- Powerful and compatible thanks to the 40 V max XGT Li-Ion battery and BL motor, which provide high power and support a 12 mm collet chuck.
- Consistent cutting with constant speed control ensuring smooth cuts, even with a ø 12 mm bit.
- Versatile plunge capacity of 60 mm, compatible with all bits in the accessory catalog, despite a lightweight and low-height design.
- Gentle stops provided by the soft brake feature, preventing damage from recoil.
- Accessory friendly and compatible with various accessories like templet guides and guide rail adapters, enhancing versatility.
- User-friendly operation with separate Lock-off and Lock-on buttons for easier use.
- Enhanced visibility provided by the LED job light, which improves visibility of the cutting position.
- Featuring also AWS, variable speed, soft start, and anti-restart functions.

TECHNICAL SPECIFICATIONS

Accumulator voltage	XGT 40 V max
No load speed	8.000 - 25.000 min ⁻¹
Base size	150 x 130 mm
Plunge capacity	60 mm
Collet size	12 mm
Dimensions (L×W×H)*	135 x 275 x 288 mm
Weight*	4,0 kg

* With BL4025 battery

ACCESSORIES

<p>Guide rail adapter 194579-2</p>	<p>Guide Rail 199140-0 (1 m), 194367-7 (3 m),</p>	<p>Clamp 199826-6 (quick type) 194385-5 (standard type)</p>
<p>Straight guide with micro adjustment 195136-9</p>	<p>Holder 122661-3</p>	<p>Rod ← 256861-8 (255 mm), 195137-7 (450 mm) →</p>
<p>Straight Guide 342428-9</p>	<p>Trimmer Guide 123022-4</p>	<p>Dust nozzle 194934-8</p>
<p>Collet cone 763622-4 (1/2")</p>	<p>Collet sleeve 763801-4 (6 mm), 763804-8 (8 mm)</p>	
<p>AWS unit WUT01 198900-7</p>	<p>Wireless unit adapter WUT02 & WUT01 199790-1</p>	



MAKITA d.o.o.,
Brnčičeva 17, 1231 Ljubljana-Črnuče, Slovenia
T: +386 (0) 59 083 600, E: info@makita.si



USER BENEFITS

- Designed to easily clear snow accumulated on pathways, entrances, sidewalks, driveways ...
- ~48 m² work area with UX01G in high mode, BL4040 battery, snow density of 150 g/l and 150 mm of snow.

TECHNICAL SPECIFICATIONS

No load speed (with UX01G, DUX60)	1.080 / 1.560 / 1.860 min ⁻¹
No load speed (with DUX18)	1.290 / 1.860 min ⁻¹
Snow clearing width	300 mm
Max snow clearing height	300 ^{*1} / 150 ^{*2} mm
Snow throwing direction adjustment	✓
Dimensions (L×W×H)	835 x 384 x 333 mm
Weight	5,0 kg

^{*1} Height equal to the height of the louvers for clearing powdery and easily collapsible snow
^{*2} Height equal to the height of the shovel for snow that is not easily collapsible

PRODUCT HIGHLIGHTS



Max. throwing distance
 12 m* with UX01G in high mode, snow density of 150 g/l and 150 mm of snow.
 * The distance varies depending on snow conditions, work speed ...



Adjustable snow direction
 The direction of snow throwing can be changed (up to 30° to the left or right) by using a lever to adjust the angle of the louvers.

NOISE AND VIBRATION

UX01G
 Sound pressure level: **81 dB(A)**, Sound power level: **91 dB(A)**, Vibration level (front/rear handle): **1,5 / 2,2 m/s²**

DUX60
 Sound pressure level: **77 dB(A)**, Sound power level: **91 dB(A)**, Vibration level (front/rear handle): **1,8 / 1,8 m/s²**

DUX18
 Sound pressure level: **78 dB(A)**, Sound power level: **90 dB(A)**, Vibration level (front/rear handle): **2,1 / 2,0 m/s²**

COMPATIBILITY

Recommended: **BL4080F, BL4050F, BL4040F, BL4040, PDC1200 and PDC1500**
 Compatible: **BL4025, BL4020, PDC01**

Recommended: **BL1840B, BL1850B, BL1860B, PDC01, PDC1200 and PDC1500**
 Compatible: **BL1815N, BL1820B, BL1830B,**

Recommended: **BL1840B, BL1850B, BL1860B and PDC01**
 Compatible: **BL1815N, BL1820B, BL1830B,**

RELATED PRODUCTS



XGT 40 V max
UX01G
 Cordless multi-function power head



LXT 18 + 18 V
DUX60
 Cordless multi-function power head



LXT 18 V
DUX18
 Cordless multi-function power head



MAKITA d.o.o.,
 Brnčičeva 17, 1231 Ljubljana-Črnuče, Slovenia
 T: +386 (0) 59 083 600, E: info@makita.si



TM001G

CORDLESS MULTI TOOL



USER BENEFITS

- Suitable for automotive technicians, electricians, plumbers, carpenters and contractors and builders
- Compatible with STARLOCK, STARLOCK PLUS and STARLOCK MAX accessories.
- High speed cutting of various materials with low vibration.
- A wide oscillation angle combined with high-speed oscillating motion results in excellent work speed.
- 12 angle setting from 0 - 360° in increments of 30°.
- Slimmer grip design has been achieved by positioning the motor vertically on the front side for a secure and comfortable grip.
- Soft start feature for smooth start-ups.

TECHNICAL SPECIFICATIONS

Accumulator voltage	40 V max XGT
Shank	STARLOCK MAX
Oscillations per minute	10.000-20.000 min ⁻¹
Oscillation angle	3,6°
Dimensions (L×W×H)*	326 x 91,5 x 123 mm
Weight*	2,1 kg

* With BL4020 battery

AVAILABLE AS

TM001GZ without battery and charger | TM001GZ03 without battery and charger and with Makpac 3 case |
 TM001GD201 with 2x BL4025 battery, DC40RA charger and Makpac 3 case

PRODUCT HIGHLIGHTS



Anti-vibration technology
 Dual housing structure with separated vibration and grip sections, cushions and damper result in low vibrations with vibration level of 2,5 m/s² or less.



Tool-less accessory clamp
 Lever style lock system allows for quick installation and replacement of the accessories.



12 angle settings
 Accessories can be positioned at every 30° increment from 0-360°.




LED job light
 Single LED with afterglow function.

ACCESSORIES

Inner tray for Makpac cases
 836313-1



Sanding pad
 B-65115



Makpac case type 3
 821551-8



Dust extraction attachment
 191R02-6



NOISE AND VIBRATION

Sound pressure level: **79 dB(A)**
 Vibration level: **2,5 m/s²**



COMPATIBILITY

Recommended: **BL4040F, BL4040, BL4025, BL4020**
 Compatible: **BL4080F, BL4050F**

RELATED PRODUCTS



LXT 18 V
DTM52
 Cordless multi tool



MAKITA d.o.o.,
 Brnčičeva 17, 1231 Ljubljana-Črnuče, Slovenia
 T: +386 (0) 59 083 600, E: info@makita.si

www.makita.si


AVAILABLE AS

UE001GZ without battery and charger

USER BENEFITS

- Suitable for gardeners, landscapers and property managers
- Output similar to 30cm³ class engine-powered edgers.
- High water-resistance.
- The automatic power-off time was revised by adding a lock lever to the lock-off lever to enhance work efficiency.
- The guard offers improved visibility of the blade tip while maintaining the coverage angle.
- The working depth can be adjusted by adjusting the tire height.
- Protects Gear case from wear due to contact with the ground during operation at the maximum cutting depth
- Variable speed control allows the user to match the speed to the application.
- Constant speed control maintains constant speed under load.
- Electric brake stops the motor rotation gently but fast, allowing user to quickly resume operation.

TECHNICAL SPECIFICATIONS

Accumulator voltage	40 V max XGT
Max output	1,1 kW
Max cutting depth	59 mm
No load speed	0-4.800 min ⁻¹
Continuous use*1	18 min (w/load)
Dimensions (L×W×H)*2	1.860 x 227 x 303 mm
Weight*2	6,1 kg

*1 With BL4050F battery | *2 With BL4020 battery

PRODUCT HIGHLIGHTS



Guard with high visibility of the blade
Guard with improved visibility of the blade tip while maintaining the coverage angle.



New lock-off mechanism
By adding a lock lever to the lock-off lever, we have revised the automatic power-off time, enhancing work efficiency.



Cutting depth adjustment
The working depth can be adjusted by adjusting the tire height.



Guard plate
Protects Gear case from wear due to contact with the ground during operation at the maximum cutting depth.

ACCESSORIES

Spare blade
196745-7


NOISE AND VIBRATION

Sound pressure level/ power level: **75,5 / 89,4 dB(A)**,
Vibration level: **2,5 m/s²**


COMPATIBILITY

Recommended: **BL4080F, BL4050F, BL4040, BL4040F, BL4025, PDC1200 and PDC1500.** Compatible: **BL4020**

RELATED PRODUCTS


XGT 40 V max
UX01G
Cordless multi function
power head



196753-8
Edger attachment



XGT 40 V max
UR003G
Cordless grass trimmer



USER BENEFITS

- Suitable for gardeners, landscapers and property managers
- Smooth and efficient trimming thanks to higher output power and higher number of strokes.
- Constant speed control suppresses rotation drop to enable stable trimming.
- Reinforced crank mechanism for reduced wear and more secure connection to the blade.
- Aluminium guide bar of the blade for lighter front end of the tool.
- Lightweight and compact for trimming and shaping smaller hedges with many curved surfaces.
- With anti-restart function to minimize accidental start-ups.

TECHNICAL SPECIFICATIONS

	UH020G	UH021G
Accumulator voltage	40 V max XGT	
Cutting strokes per minute	4.200 min ⁻¹	
Blade length	500 mm	600 mm
Maximum cutting diameter	20 mm	
Dimensions (L×W×H)	929 x 207 x 185 mm	1.048 x 207 x 185 mm
Weight*	3,0 kg	3,1 kg

* With BL4020 battery

AVAILABLE AS

UH020GZ without battery and charger | UH021GZ without battery and charger


PRODUCT HIGHLIGHTS



Blade type
With triple ground teeth and design that secures the branch in place for smooth cutting.



LED indicator
Warns the user in case of overheating or battery over-discharge.



Reverse function for clearing jammed branches
By pressing the reverse button and pulling the trigger the blades reverse for a moment to clear a jammed branch.



Chip receiver (optional)
Catches chips for easier clean-up.

ACCESSORIES

Shear blade
1914G4-7 - UH020G
1914G5-5 - UH021G

Blade cover
413L91-8 - UH020G
413L92-6 - UH021G



Chip receiver
1910T1-0 - UH020G
1910T2-8 - UH021G

Grease
199450-5



NOISE AND VIBRATION

Sound pressure / power level: **83 / 93 dB(A)**
Vibration level: **2,5 m/s²**



COMPATIBILITY

Recommended: **BL4040F, BL4040, BL4025, BL4020, PDC1500, PDC1200, PDC01** Compatible: **BL4080F, BL4050F**

RELATED PRODUCTS



LXT 18 V
DUH606/DUH506
Cordless hedge trimmer



LXT 18 V
DUH607/DUH507
Cordless hedge trimmer



MAKITA d.o.o.,
Brnčičeva 17, 1231 Ljubljana-Črnuče, Slovenia
T: +386 (0) 59 083 600, E: info@makita.si

www.makita.si



UN001G

CORDLESS POLE HEDGE TRIMMER



AVAILABLE AS

UN001GZ without battery and charger

USER BENEFITS

- Suitable for gardeners and arborists
- Capable of cutting thick branches with high power, comparable to engine models.
- Lightest in its class, offering excellent usability.
- Equipped with a grease nipple for easy maintenance.
- Higher operator's convenience has been achieved by drastically reducing the weight of the tool compared to competing engine models.
- Three-facet obliquely ground blade.
- Improved durability of angle adjustment section
- Lubrication is possible with a grease gun.
- Reverse rotation system frees the blades when it is jammed by thick branches.
- 3-speed design for optimum speed control
- Angle adjustable hedge trimmer head; 45° tilt-up to 70° tilt-down from the horizontal position.
- Can be folded in the 180° position for easy transport and storage.

TECHNICAL SPECIFICATIONS

Accumulator voltage	40 V max XGT
No load speed	1.000/1.500/2.000 min ⁻¹
Cutting strokes per minute	2.000/3.000/4.000 min ⁻¹
Blade length	600 mm
Max cutting diameter	20 mm
Dimensions (L×W×H)	2.268 x 100 x 148 mm
Weight* ¹	4,7 kg

* With BL4020 battery

PRODUCT HIGHLIGHTS



Designed to be lightweight and capable of cutting thick branches
Due to an increased power obtained by the 40Vmax XGT li-ion battery and thick shear blades is capable of cutting thick branches. Higher operator's convenience has been achieved by drastically reducing the weight of the tool compared to competing engine models.



Lubrication is possible with a grease gun
Maintenance efficiency has been improved by adding a grease nipple and allowing oil to be supplied with a grease gun without removing the bolt on the oil supply port. Users who do not own a grease gun can remove the bolt and supply grease with a grease tube as with our current models.



Improved durability of Angle adjustment section
• Two brass washers are installed on both sides, and the brass washers slide against each other to prevent wear of the tool body, reducing backlash.
• A steel sleeve is added to the hole in the case of the tool body where angle adjustment pin is inserted to prevent wear of the hole.



Three-facet obliquely ground blade
Double-sided rough-cut type.

ACCESSORIES

Pole hedge trimmer blade 1914E7-7	Chip receiver 1910T2-8	Blade cover 458414-1
Machine grease 199450-5	Shoulder strap 122D94-0	

NOISE AND VIBRATION

Sound pressure / power level: **82 / 93 dB(A)**
Vibration level: **4,9 m/s²**

COMPATIBILITY

Recommended: **BL4020, BL4025, BL4040, BL4040F, BL4050F, BL4080F, PDC01, PDC1200 and PDC1500**

RELATED PRODUCTS



LXT 18 V
DUN500
Cordless Hedge Trimmer



LXT 18 V
DUN461
Cordless Pole Hedge Trimmer



XGT 40 V max
UX01G
Cordless multi function power head



196257-0
Attachment for multi function power head



MAKITA d.o.o.,
Brnčičeva 17, 1231 Ljubljana-Črnuče, Slovenia
T: +386 (0) 59 083 600, E: info@makita.si

www.makita.si